



TECHNICAP

216, Chemin du Braousch - 06320 La Turbie / France
 Tél : 33 (0)4 92 10 85 68 - Fax : 33 (0)4 92 10 82 98
 Email : technicap@wanadoo.fr / www.technicap.com

MODEL	PPS 3/3	
Collecting area (sqm)	0,125	
Shape	Cylindro-conical	
Baffle material	Phenolic Composite	
Baffle Cell diameter	9,5mm	
Aspect ratio of a cell	5,26	
Number of Samples	12	
Volume of Sampling Bottles	250ml or 500ml	
Sampling Interval	Minimum 1 minute	
Max. continuous deployment	18 months (24 months with Lithium batteries)	
Opérating Temperature	-2° to 37°	
Maximum Operating Deph	1000m (PETP) or 5000m (Aluminium) or 6000m (Titanium)	
MATERIALS		
Trap body	Glass reinforced polyester (GRP) on an alimentary gel-coat	
Carrousel	PETP (very hard thermoplastic)	
Sampling Bottles	Polypropylen	
Electronics / Motor pressure case	Thermoplastic (PETP/PEEK) or Aluminium alloy anodizing or Titanium	
Rotating Mooring Bar	Titanium	
Power Supply	12 volt AA alkaline batteries pack (or 12 volt lithium on request)	
Drive motor torque	60kg/cm	
Time to shift a bottle	7 seconds	
Communications	Electronic card and firmware with integrated inclinometer and temperature sensors	
DIMENSIONS with:	250ml bottles	500ml bottles
Height	1900 mm	2040 mm
Diameter Max	600 mm	600 mm
WEIGHT with PETP motor, rotary disk and empty bottles		
In Air	48 kg	52,2 kg
In Water	26,7 kg	29,1 kg
DELIVERY : WOOD BOX		
External Dimensions	2000 x 560 x 750 mm	2140 x 560 x 750 mm
Total Weight approx.	90 kg	96 kg